

JIS C-3501 Coaxial (50 Ohms)

KCI

5D-2V	
Construction Data	
Conductor : Type No of wires x Wire Diameter (mm)	Plain Copper 1x1.4
Insulation : Type	Solid PE
Diameter Over Insulation (mm)	4.8
Shield	Braid of Plain Copper Wires
Jacket (Type)	PVC
Overall Diameter (mm)	7.3
Total Weight (kg/kM)	80
Electrical Data	
(Characteristic) Impedance Z(Ohm)	50 +/-2
Capacitance (pF/m)	100 +/- 4
Conductor DC Resistance (Ohm/km) @20°C	11.7
Test Voltage (V rms)	1000
Attenuation (db/kM , @ 10MHz)	27



5D-2W	
Construction Data	
Conductor : Type No of wires x Wire Diameter (mm)	Plain Copper 1x1.4
Insulation : Type	Solid PE
Diameter Over Insulation (mm)	4.8
Shield	Double layer Braid of Plain Copper Wires
Jacket (Type)	PVC
Overall Diameter (mm)	8.0
Total Weight (kg/kM)	108
Electrical Data	
(Characteristic) Impedance Z(Ohm)	50 +/-2
Capacitance (pF/m)	100 +/- 4
Conductor DC Resistance (Ohm/km) @20°C	11.7
Test Voltage (V rms)	1000
Attenuation (db/kM , @ 10MHz)	27

