

Special Coaxial

7 Cores 1.5C-2V	
Construction Data	
Conductor : Type No of wires x Wire Diameter (mm)	Copper Clad Steel 1x0.26
Insulation : Type	Solid PE
Diameter Over Insulation (mm)	1.6
Shield	Braid of Plain Copper Wires
Individual Jacket (Type) / Coaxial OD	PVC / 3.0
Overall Jacket (Type) / Diameter (mm)	PVC / 11.4
Total Weight (kg/kM)	154
Electrical Data	
(Characteristic) Impedance Z(Ohm)	75 +/-3
Capacitance (pF/m)	69 +/- 4
Test Voltage (V rms)	1000
Attenuation (db/kM , @ 10MHz)	96



16 Cores 1.5C-2V	
Construction Data	
Conductor : Type No of wires x Wire Diameter (mm)	Copper Clad Steel 1x0.26
Insulation : Type	Solid PE
Diameter Over Insulation (mm)	1.6
Shield	Braid of Plain Copper Wires
Individual Jacket (Type) / Coaxial OD	PVC / 3.0
Overall Jacket (Type) / Diameter (mm)	PVC / 16.7
Total Weight (kg/kM)	330
Electrical Data	
(Characteristic) Impedance Z(Ohm)	75 +/-3
Capacitance (pF/m)	69 +/- 4
Test Voltage (V rms)	1000
Attenuation (db/kM , @ 10MHz)	96

