

NYSLYCYO-J Control Oil Resistant

VDE 0250 P.405 300/500 V



These cables are used as control or power cable for machine, machine-tool or elevator construction, as well as for heating and cooling machine, assembly and production lines.

They are manufactured in acc. with VDE 0250-Part 405 type NYSLYCYO-J

Conductor	Plain annealed copper conductor class 5
-----------	---

Color Code :



Black with sequential numbering with green & yellow insulated earth wire

Insulation	PVC insulation type YI 2
------------	--------------------------


Inner Jacket	PVC
--------------	-----

Shield (Screen)	Braid of Tinned Copper Wires
-----------------	------------------------------

Over-Sheath	PVC sheath type YM 2
-------------	----------------------



Flexible




+70 °C



IEC 60332-1



7.5 x O.D



Oil-Resistant



Screened

Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	Kg/Km	meter
18x0.5	0.6	1.5	16.8	397	1000
18x0.75	0.6	1.5	17.7	466	1000
18x1.0	0.6	1.8	19.2	555	1000
18x1.5	0.6	1.8	20.6	674	1000
18x2.5	0.7	2.1	24.9	1,014	500
25x0.5	0.6	1.8	19.6	518	1000
25x0.75	0.6	1.8	20.7	607	1000
25x1.0	0.6	1.8	22.1	719	1000
25x1.5	0.6	2.1	24.4	910	1000
25x2.5	0.7	2.1	29.0	1,357	500

NYSLYCYO-J Control Oil Resistant

VDE 0250 P.405 300/500 V

Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	Kg/Km	meter
34x0.5	0.6	1.8	21.8	658	1000
34x0.75	0.6	1.8	23.4	802	1000
34x1.0	0.6	2.1	25.2	958	500
34x1.5	0.6	2.1	27.4	1,208	500
34x2.5	0.7	2.4	33.0	1,817	500
50x0.5	0.6	2.1	26.0	940	500
50x0.75	0.6	2.1	27.6	1,121	500
50x1.0	0.6	2.1	29.4	1,324	500
50x1.5	0.6	2.4	32.3	1,675	500
50x2.5	0.7	2.7	38.9	2,517	500
61x0.5	0.6	2.1	27.3	1,064	500
61x0.75	0.6	2.1	29.3	1,298	500
61x1.0	0.6	2.4	31.5	1,553	500
61x1.5	0.6	2.4	34.0	1,920	500
61x2.5	0.7	2.7	41.1	2,958	500