




<b>Conductor</b>	Stranded (class 2) Plain annealed copper wires 35 mm <sup>2</sup> and above compacted conductor
------------------	--

Color Code Options :



Preferred : Black or Red

<b>Insulation</b>	PVC
<b>Over-Sheath</b>	Extruded PVC



+70 °C

IEC 60332-1

15 x O.D

Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm <sup>2</sup>	mm	mm	mm	Kg/Km	meter
1x4 rm	1.0	1.4	7.4	91	1000
1x6 rm	1.0	1.4	7.9	116	1000
1x10 rm	1.0	1.4	8.9	165	1000
1x16 rm	1.0	1.4	9.9	232	1000
1x25 rm	1.2	1.4	11.6	334	1000
1x35 rm	1.2	1.4	12.2	418	1000
1x50 rm	1.4	1.4	13.8	574	1000
1x70 rm	1.4	1.4	15.5	770	1000
1x95 rm	1.6	1.5	17.7	1,031	1000
1x120 rm	1.6	1.5	19.2	1,270	1000
1x150 rm	1.8	1.6	21.3	1,580	1000
1x185 rm	2.0	1.7	23.5	1,941	1000
1x240 rm	2.2	1.8	26.5	2,495	1000
1x300 rm	2.4	1.9	29.2	3,094	500
1x400 rm	2.6	2.0	32.4	4,059	500
1x500 rm	2.8	2.1	36.1	5,042	500
1x630 rm	2.8	2.2	42.8	6,591	500