

Conductor	Stranded (class 2) Plain annealed copper wires sector shaped for 50 mm ² and above
------------------	---

Color Code Options :



Insulation	PVC
Inner Covering (Filler)	Extruded PVC (for round shaped conductor) and yarns & Binder Tape for sector shaped ones.
Over-Sheath	Extruded PVC



Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	Kg/Km	meter
2x1.5 rm	0.8	1.8	11.2	181	1000
2x2.5 rm	0.8	1.8	12.0	221	1000
2x4 rm	1.0	1.8	14.3	323	1000
2x6 rm	1.0	1.8	15.4	398	1000
2x10 rm	1.0	1.8	17.3	541	1000
2x16 rm	1.0	1.8	19.8	756	1000
2x25 rm	1.2	1.8	23.2	1,145	1000
2x35 rm	1.2	1.8	24.4	1,287	1000
2x50 sm	1.4	1.8	22.9	1,214	1000
2x70 sm	1.4	1.9	26.2	2,075	1000
2x95 sm	1.6	2.0	30.0	2,169	500
2x120 sm	1.6	2.1	33.0	2,679	500
2x150 sm	1.8	2.2	36.6	3,318	500
2x185 sm	2.0	2.4	40.5	4,078	500
2x240 sm	2.2	2.6	45.7	5,236	500
2x300 sm	2.4	2.7	50.5	6,475	500
2x400 sm	2.6	3.0	57.8	8,416	500