



<b>Conductor</b>	Stranded (class 2) Plain annealed copper wires sector shaped for 50 mm <sup>2</sup> and above
Color Code Options :	
 EN/BSI/IEC	 BSI
 VDE/IEC	
<b>Insulation</b>	PVC
<b>Inner Covering (Filler)</b>	Extruded PVC (for round shaped conductor) and yarns & Binder Tape for sector shaped ones.
<b>Over-Sheath</b>	Extruded PVC



Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm <sup>2</sup>	mm	mm	mm	Kg/Km	meter
3x1.5 rm	0.8	1.8	11.7	204	1000
3x2.5 rm	0.8	1.8	12.6	252	1000
3x4 rm	1.0	1.8	15.0	373	1000
3x6 rm	1.0	1.8	16.2	467	1000
3x10 rm	1.0	1.8	18.2	649	1000
3x16 rm	1.0	1.8	20.9	920	1000
3x25 rm	1.2	1.8	24.6	1,317	1000
3x35 rm	1.2	1.8	25.8	1,605	1000
3x50 sm	1.4	1.8	25.9	1,815	500
3x70 sm	1.4	2.0	29.2	2,436	500
3x95 sm	1.6	2.1	33.3	3,242	500
3x120 sm	1.6	2.2	36.1	3,990	500
3x150 sm	1.8	2.3	40.1	4,948	500
3x185 sm	2.0	2.5	44.4	6,080	500
3x240 sm	2.2	2.7	49.8	7,802	500
3x300 sm	2.4	2.9	52.2	9,639	500
3x400 sm	2.6	3.1	59.5	12,677	250