




Conductor	Stranded (class 2) Plain annealed copper wires 35 mm ² and above compacted conductor
------------------	--

Color Code Options :



Preferred : Black or Red

Insulation	XLPE
Over-Sheath	Extruded PVC



Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	Kg/Km	meter
1x4 rm	0.7	1.4	6.8	78	1000
1x6 rm	0.7	1.4	7.3	101	1000
1x10 rm	0.7	1.4	8.3	147	1000
1x16 rm	0.7	1.4	9.3	211	1000
1x25 rm	0.9	1.4	11.0	309	1000
1x35 rm	0.9	1.4	11.6	391	1000
1x50 rm	1.0	1.4	13.0	537	1000
1x70 rm	1.1	1.4	14.9	732	1000
1x95 rm	1.1	1.5	16.7	973	1000
1x120 rm	1.2	1.5	18.4	1,212	1000
1x150 rm	1.4	1.6	20.5	1,511	1000
1x185 rm	1.6	1.6	22.5	1,848	1000
1x240 rm	1.7	1.7	25.3	2,375	1000
1x300 rm	1.8	1.8	27.8	2,946	1000
1x400 rm	2.0	1.9	31.0	3,886	500
1x500 rm	2.2	2.0	34.7	4,839	500
1x630 rm	2.4	2.2	42.0	6,403	500