

Conductor	Stranded (class 2) Plain annealed copper wires sector shaped for 50 mm ² and above
-----------	---

Color Code Options :



Insulation	XLPE
Inner Covering (Filler)	Extruded PVC (for round shaped conductor) and yarns & Binder Tape for sector shaped ones.
Over-Sheath	Extruded PVC



Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	Kg/Km	meter
2x1.5 rm	0.7	1.8	10.8	164	1000
2x2.5 rm	0.7	1.8	11.6	202	1000
2x4 rm	0.7	1.8	13.1	273	1000
2x6 rm	0.7	1.8	14.2	342	1000
2x10 rm	0.7	1.8	16.1	476	1000
2x16 rm	0.7	1.8	18.6	665	1000
2x25 rm	0.9	1.8	22.0	984	1000
2x35 rm	0.9	1.8	23.2	1,190	1000
2x50 sm	1.0	1.8	20.8	1,147	1000
2x70 sm	1.1	1.8	23.7	1,530	1000
2x95 sm	1.1	2.0	27.1	2,037	1000
2x120 sm	1.2	2.1	30.1	2,541	500
2x150 sm	1.4	2.2	33.3	3,153	500
2x185 sm	1.6	2.3	36.7	3,863	500
2x240 sm	1.7	2.5	41.4	4,962	500
2x300 sm	1.8	2.7	45.9	6,158	500
2x400 sm	2.0	2.9	52.3	8,133	500