



Conductor	Stranded (class 2) Plain annealed copper wires sector shaped for 50 mm ² and above
Color Code Options :	
<p>EN/BSI/IEC</p>	<p>BSI</p>
<p>VDE/IEC</p>	
Insulation	XLPE
Inner Covering (Filler)	Extruded PVC (for round shaped conductor) and yarns & Binder Tape for sector shaped ones.
Over-Sheath	Extruded PVC



Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	Kg/Km	meter
3x1.5 rm	0.7	1.8	11.2	183	1000
3x2.5 rm	0.7	1.8	12.1	230	1000
3x4 rm	0.7	1.8	13.7	315	1000
3x6 rm	0.7	1.8	14.9	402	1000
3x10 rm	0.7	1.8	16.9	573	1000
3x16 rm	0.7	1.8	19.6	830	1000
3x25 rm	0.9	1.8	23.3	1,210	1000
3x35 rm	0.9	1.8	24.5	1,491	1000
3x50 sm	1.0	1.8	24.1	1,674	1000
3x70 sm	1.1	1.9	27.7	2,279	1000
3x95 sm	1.1	2.0	30.9	3,007	500
3x120 sm	1.2	2.1	34.2	3,753	500
3x150 sm	1.4	2.3	38.3	4,684	500
3x185 sm	1.6	2.4	42.4	5,746	500
3x240 sm	1.7	2.6	47.4	7,372	500
3x300 sm	1.8	2.8	49.4	9,103	500
3x400 sm	2.0	3.1	56.8	12,063	250