

Conductor	Stranded (class 2) Plain annealed copper wires sector shaped for 50 mm <sup>2</sup> and above
Color Code Options :	
EN/BSI/IEC	BSI
VDE/IEC	
Insulation	XLPE
Inner Covering (Filler)	Extruded PVC (for round shaped conductor) and yarns & Binder Tape for sector shaped ones.
Over-Sheath	Extruded PVC



Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm <sup>2</sup>	mm	mm	mm	Kg/Km	meter
3x25/16 rm	0.9	1.8	24.4	1,369	1000
3x35/16 rm	0.9	1.8	25.4	1,652	1000
3x50/25 sm/rm	1.0	1.8	25.6	1,952	1000
3x70/35 sm	1.1	1.9	29.3	2,660	500
3x95/50 sm	1.1	2.1	33.0	3,551	500
3x120/70 sm	1.2	2.2	36.6	4,493	500
3x150/70 sm	1.4	2.3	40.8	5,421	500
3x185/95 sm	1.6	2.5	45.3	6,740	500
3x240/120 sm	1.7	2.7	50.7	8,658	500
3x300/150 sm	1.8	2.8	55.9	10,707	250