



<b>Conductor</b>	Stranded (class 2) Plain annealed copper wires sector shaped for 50 mm <sup>2</sup> and above
Color Code Options :	
EN/BSI/IEC	BSI
	VDE/IEC
<b>Insulation</b>	XLPE
<b>Inner Covering (Filler)</b>	Extruded PVC (for round shaped conductor) and yarns & Binder Tape for sector shaped ones.
<b>Over-Sheath</b>	Extruded PVC



Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm <sup>2</sup>	mm	mm	mm	Kg/Km	meter
4x1.5 rm	0.7	1.8	12.0	212	1000
4x2.5 rm	0.7	1.8	13.0	269	1000
4x4 rm	0.7	1.8	14.7	372	1000
4x6 rm	0.7	1.8	16.1	481	1000
4x10 rm	0.7	1.8	18.3	695	1000
4x16 rm	0.7	1.8	21.3	1,015	1000
4x25 rm	0.9	1.8	25.4	1,490	1000
4x35 rm	0.9	1.8	26.8	1,852	1000
4x50 sm	1.0	1.9	26.9	2,204	1000
4x70 sm	1.1	2.0	30.8	3,005	500
4x95 sm	1.1	2.1	34.4	3,970	500
4x120 sm	1.2	2.3	38.4	4,977	500
4x150 sm	1.4	2.4	42.8	6,190	500
4x185 sm	1.6	2.6	47.5	7,621	500
4x240 sm	1.7	2.8	53.1	9,778	500
4x300 sm	1.8	3.0	58.8	12,127	250
4x400 sm	2.0	3.3	66.2	16,042	250

Power Cables