

Conductor	Stranded (class 2) Plain annealed copper wires
Color Code Options :	Optional green & yellow insulated earth wire
<p>Black (Numbered)</p>	<p>(type NYCY-J)</p>
Insulation	PVC
Inner Covering (Filler)	Extruded PVC
Concentric Conductor	Copper Wires
Over-Sheath	Extruded PVC



Nominal cross section area of conductor	Insulation Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	Kg/Km	meter
5x1.5rm/1.5	0.8	1.8	15.0	316	1000
5x2.5rm/2.5	0.8	1.8	16.2	401	1000
6x1.5rm/1.5	0.8	1.8	16.0	358	1,000
7x1.5rm/2.5	0.8	1.8	16.0	381	1,000
10x1.5rm/2.5	0.8	1.8	19.2	550	1,000
12x1.5rm/2.5	0.8	1.8	19.8	530	1,000
14x1.5rm/2.5	0.8	1.8	20.6	589	1,000
16x1.5rm/4	0.8	1.8	21.8	670	1,000
19x1.5rm/4	0.8	1.8	22.8	748	1,000
24x1.5rm/6	0.8	1.8	25.9	929	500
30x1.5rm/6	0.8	1.8	27.3	1,088	500