

Cu/PVC/PVC/PVC/AWA/PVC



IEC 60502-1 0.6/1 kV




Conductor	Stranded (class 2) Plain annealed copper wires 35 mm ² and above compacted conductor
-----------	--

Color Code Options :



Preferred : Black or Red

Insulation	PVC
Inner Covering (Bedding)	Extruded PVC
Armour	Aluminium Wires
Over-Sheath	Extruded PVC



+70 °C



IEC 60332-1



15x O.D



Armoured

Nominal cross section area of conductor	Insulation Thickness	Diameter Under Armour	Armour Wire Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	mm	mm	Kg/Km	meter
1x25 rm	1.2	10.8	1.25	1.8	16.9	542	1000
1x35 rm	1.2	11.4	1.25	1.8	17.5	636	1000
1x50 rm	1.4	13.0	1.25	1.8	19.1	818	1000
1x70 rm	1.4	14.7	1.25	1.8	20.8	1,040	1000
1x95 rm	1.6	16.7	1.25	1.8	22.8	1,321	1000
1x120 rm	1.6	18.2	1.6	1.8	25.0	1,640	1000
1x150 rm	1.8	20.1	1.6	1.8	26.9	1,971	1000
1x185 rm	2.0	22.1	1.6	1.8	28.9	2,355	1000
1x240 rm	2.2	24.9	1.6	1.9	31.9	2,950	1000
1x300 rm	2.4	27.4	2.0	2.0	35.4	3,684	500
1x400 rm	2.6	30.8	2.0	2.1	39.0	4,748	500
1x500 rm	2.8	34.3	2.0	2.2	42.7	5,811	500
1x630 rm	2.8	36.8	2.0	2.4	45.6	7,083	500

Power Cables