

<b>Conductor</b>	Stranded (class 2) Plain annealed copper wires sector shaped for 50 mm <sup>2</sup> and above
------------------	---

Color Code Options :



<b>Insulation</b>	PVC
-------------------	-----

<b>Inner Covering (Bedding)</b>	Extruded PVC
---------------------------------	--------------

<b>Armour</b>	Galvanized Steel Wires
---------------	------------------------

<b>Over-Sheath</b>	Extruded PVC
--------------------	--------------



Nominal cross section area of conductor	Insulation Thickness	Diameter Under Armour	Armour Wire Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm <sup>2</sup>	mm	mm	mm	mm	mm	Kg/Km	meter
3x25/16 rm	1.2	22.2	1.6	1.8	29.0	2,195	500
3x35/16 rm	1.2	23.3	1.6	1.9	30.3	2,513	1000
3x50/25 sm/rm	1.4	25.8	2.0	2.0	33.8	3,390	500
3x70/35 sm	1.4	29.3	2.0	2.1	37.5	4,300	500
3x95/50 sm	1.6	33.5	2.0	2.3	42.1	5,496	500
3x120/70 sm	1.6	36.8	2.5	2.5	46.8	7,054	500
3x150/70 sm	1.8	40.8	2.5	2.6	51.0	8,295	500
3x185/95 sm	2.0	45.0	2.5	2.7	55.4	9,918	500
3x240/120 sm	2.2	50.8	2.5	2.9	61.6	12,319	250
3x300/150 sm	2.4	56.2	2.5	3.1	67.4	14,835	250