

Conductor	Stranded (class 2) Plain annealed copper wires 35 mm ² and above compacted conductor
------------------	--

Color Code Options :




Insulation	PVC
-------------------	-----

Inner Covering (Bedding)	Extruded PVC
---------------------------------	--------------

Armour	Galvanized Steel Wires
---------------	------------------------

Over-Sheath	Extruded PVC
--------------------	--------------



Nominal cross section area of conductor	Insulation Thickness	Diameter Under Armour	Armour Wire Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	mm	mm	Kg/Km	meter
5x1.5 rm	0.8	10.6	0.9	1.8	16.0	504	1000
5x2.5 rm	0.8	11.8	0.9	1.8	17.2	601	1000
5x4 rm	1.0	14.3	1.25	1.8	20.4	919	1000
5x6 rm	1.0	15.8	1.25	1.8	21.9	1,093	1000
5x10 rm	1.0	18.3	1.6	1.8	25.1	1,586	500
5x16 rm	1.0	21.2	1.6	1.8	28.0	2,033	1000
5x25 rm	1.2	25.8	1.6	1.9	32.8	2,817	500
5x35 rm	1.2	27.4	2.0	2.0	35.4	3,558	500
5x50 rm	1.4	32.1	2.0	2.2	40.5	4,703	500
5x70 rm	1.4	36.7	2.0	2.3	45.3	6,025	500
5x95 rm	1.6	42.5	2.5	2.5	52.5	8,257	500
5x120 rm	1.6	46.5	2.5	2.7	56.9	9,884	500
5x150 rm	1.8	52.1	2.5	2.9	62.9	11,992	250
5x185 rm	2.0	57.5	2.5	3.0	68.5	14,287	250
5x240 rm	2.2	65.0	3.2	3.3	77.9	18,782	250