



Conductor	Stranded (class 2) Plain annealed copper wires sector shaped for 50 mm ² and above
------------------	---

Color Code Options :



EN/BSI/IEC



BSI




VDE/IEC

Insulation	PVC
-------------------	-----

Inner Covering (Bedding)	Extruded PVC
---------------------------------	--------------

Armour	Galvanized Steel Tapes
---------------	------------------------

Over-Sheath	Extruded PVC
--------------------	--------------



+70 °C



IEC 60332-1



12x O.D



Armoured

Nominal cross section area of conductor	Insulation Thickness	Diameter Under Armour	Armour Tape Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	mm	mm	Kg/Km	meter
3x1.5 rm	0.8	9.3	0.2	1.8	13.7	304	1000
3x2.5 rm	0.8	10.2	0.2	1.8	14.6	359	1000
3x4 rm	1.0	12.2	0.2	1.8	16.6	477	1000
3x6 rm	1.0	13.4	0.2	1.8	17.8	578	1000
3x10 rm	1.0	15.4	0.2	1.8	19.8	770	1000
3x16 rm	1.0	17.7	0.2	1.8	22.1	1,027	1000
3x25 rm	1.2	21.4	0.2	1.8	25.8	1,434	1000
3x35 rm	1.2	22.6	0.2	1.8	27.0	3,919	1000
3x50 sm	1.4	24.7	0.2	1.9	29.3	2,173	500
3x70 sm	1.4	27.6	0.2	2.0	32.4	2,821	500
3x95 sm	1.6	31.5	0.5	2.2	37.9	4,079	500
3x120 sm	1.6	34.1	0.5	2.3	40.7	4,895	500
3x150 sm	1.8	38.3	0.5	2.4	45.1	5,995	500
3x185 sm	2.0	42.2	0.5	2.6	49.4	7,230	500
3x240 sm	2.2	47.4	0.5	2.8	55.0	9,116	500
3x300 sm	2.4	49.6	2.5	2.9	60.4	12,609	250