

<b>Conductor</b>	Stranded (class 2) Plain annealed copper wires sector shaped for 50 mm <sup>2</sup> and above
------------------	---

Color Code Options :



<b>Insulation</b>	PVC
-------------------	-----

<b>Inner Covering (Bedding)</b>	Extruded PVC
---------------------------------	--------------

<b>Armour</b>	Galvanized Steel Tapes
---------------	------------------------

<b>Over-Sheath</b>	Extruded PVC
--------------------	--------------



Nominal cross section area of conductor	Insulation Thickness	Diameter Under Armour	Armour Tape Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm <sup>2</sup>	mm	mm	mm	mm	mm	Kg/Km	meter
3x25/16 rm	1.2	22.6	0.2	1.8	27.0	1,642	1000
3x35/16 rm	1.2	23.7	0.2	1.8	28.1	1,921	1000
3x50/25 sm/rm	1.4	26.2	0.2	2.0	31.0	2,508	500
3x70/35 sm	1.4	29.3	0.2	2.1	34.3	3,284	500
3x95/50 sm	1.6	33.5	0.5	2.3	40.1	4,740	500
3x120/70 sm	1.6	36.8	0.5	2.3	43.4	5,785	500
3x150/70 sm	1.8	40.8	0.5	2.5	47.8	6,931	500
3x185/95 sm	2.0	45.2	0.5	2.7	52.6	8,474	500
3x240/120 sm	2.2	50.8	0.5	2.9	58.6	10,663	250
3x300/150 sm	2.4	56.4	0.5	3.1	64.6	13,063	250