


Conductor	Stranded (class 2) Plain annealed copper wires sector shaped for 50 mm ² and above
-----------	---

Color Code Options :



Insulation	PVC
Inner Covering	Extruded PVC
Metal Sheath	Lead Sheath (Cover)
Inner Covering (Bedding)	Extruded PVC
Armour	Galvanized Steel Wires
Over-Sheath	Extruded PVC



Nominal cross section area of conductor	Diameter Under Armour	Armour Wire Diameter	Diameter Over Lead Sheath	Lead Sheath Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	mm	mm	mm	Kg/Km	meter
2x1.5 rm	12.8	1.25	10.8	1.2	1.8	18.9	1,030	1000
2x2.5 rm	13.6	1.25	11.6	1.2	1.8	19.7	1,128	1000
2x4 rm	15.5	1.25	13.5	1.2	1.8	21.6	1,347	1000
2x6 rm	16.6	1.25	14.6	1.2	1.8	22.7	1,491	1000
2x10 rm	18.5	1.6	16.5	1.2	1.8	25.3	1,905	1000
2x16 rm	20.6	1.6	18.6	1.2	1.8	27.4	2,250	1000
2x25 rm	24.0	1.6	22.0	1.2	1.9	31.0	2,815	1000
2x35 rm	25.4	1.6	23.4	1.3	1.9	32.4	3,203	1000
2x50 sm	26.1	2.0	23.9	1.3	2.1	34.3	3,694	1000
2x70 sm	29.6	2.0	27.2	1.4	2.2	38.0	4,632	1000
2x95 sm	33.3	2.0	30.9	1.5	2.4	42.1	5,616	1000
2x120 sm	37.0	2.5	34.4	1.6	2.5	47.0	7,040	1000
2x150 sm	40.8	2.5	38.0	1.7	2.6	51.0	8,288	500
2x185 sm	45.1	2.5	42.1	1.8	2.8	55.7	9,581	500
2x240 sm	50.3	2.5	47.1	1.9	3.0	61.3	11,474	500
2x300 sm	55.9	2.5	52.5	2.1	3.2	67.3	13,796	500