


Conductor	Stranded (class 2) Plain annealed copper wires 35 mm ² and above compacted conductor
------------------	--

Color Code Options :



Insulation	PVC
Inner Covering	Extruded PVC
Metal Sheath	Lead Sheath (Cover)
Inner Covering (Bedding)	Extruded PVC
Armour	Galvanized Steel Wires
Over-Sheath	Extruded PVC



Nominal cross section area of conductor	Diameter Under Armour	Armour Wire Diameter	Diameter Over Lead Sheath	Lead Sheath Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	mm	mm	mm	Kg/Km	meter
5x1.5 rm	15.0	1.25	13.0	1.2	1.8	21.1	1,284	1000
5x2.5 rm	16.2	1.25	14.2	1.2	1.8	22.3	1,441	1000
5x4 rm	18.7	1.6	16.7	1.2	1.8	25.5	1,912	1000
5x6 rm	20.2	1.6	18.2	1.2	1.8	27.0	2,175	1000
5x10 rm	22.7	1.6	20.7	1.2	1.8	29.5	2,648	1000
5x16 rm	25.8	1.6	23.8	1.3	1.9	32.8	3,335	1000
5x25 rm	30.8	2.0	28.6	1.4	2.1	39.0	4,739	1000
5x35 rm	32.8	2.0	30.4	1.5	2.2	41.2	5,492	1000
5x50 rm	37.9	2.5	35.3	1.6	2.4	47.7	7,502	500
5x70 rm	38.1	2.5	35.5	1.7	2.6	48.3	8,614	500
5x95 rm	49.3	2.5	46.3	1.9	2.8	59.9	11,912	250
5x120 rm	49.5	2.5	46.5	2.0	2.9	60.3	13,268	250
5x150 rm	59.5	2.5	56.3	2.1	3.1	70.7	16,769	250
5x185 rm	65.7	3.2	62.1	2.3	3.4	78.8	20,952	250
5x240 rm	73.8	3.2	70.0	2.5	3.6	87.3	25,340	250