





Conductor	Stranded (class 2) Plain annealed copper wires
Color Code Options :	Optional green & yellow insulated earth wire
 Black (Numbered)	 (type NYKYRY-J)
Insulation	PVC
Inner Covering	Extruded PVC
Metal Sheath	Lead Sheath (Cover)
Inner Covering (Bedding)	Extruded PVC
Armour	Galvanized Steel Wires
Over-Sheath	Extruded PVC



Nominal cross section area of conductor	Diameter Under Armour	Armour Wire Diameter	Diameter Over Lead Sheath	Lead Sheath Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	mm	mm	mm	Kg/Km	meter
6x1.5 rm	16.0	1.25	14.0	1.2	1.8	22.1	1,400	1000
7x1.5 rm	16.0	1.25	14.0	1.2	1.8	22.1	1,413	1000
8x1.5 rm	17.9	1.6	15.9	1.2	1.8	24.7	1,800	1000
9x1.5 rm	18.0	1.6	16.0	1.2	1.8	24.8	1,797	1000
10x1.5 rm	19.2	1.6	17.2	1.2	1.8	26.0	1,943	1000
12x1.5 rm	19.6	1.6	17.6	1.2	1.8	26.4	2,026	1000
14x1.5 rm	20.6	1.6	18.6	1.2	1.8	27.3	2,157	1000
16x1.5 rm	21.5	1.6	19.5	1.2	1.8	28.3	2,246	1000
19x1.5 rm	22.5	1.6	20.5	1.2	1.8	29.3	2,384	500
21x1.5 rm	23.5	1.6	21.5	1.2	1.9	30.5	2,538	500
24x1.5 rm	25.9	1.6	23.9	1.3	1.9	32.9	2,906	500
27x1.5 rm	26.4	1.6	24.4	1.3	1.9	33.4	3,023	1000
30x1.5 rm	27.4	1.6	25.2	1.3	2.0	34.6	3,192	500
37x1.5 rm	29.5	2.0	27.3	1.4	2.1	37.7	3,911	500
40x1.5 rm	30.7	2.0	28.3	1.4	2.1	38.9	4,118	500
50x1.5 rm	34.8	2.0	32.4	1.5	2.2	43.2	4,953	500
61x1.5 rm	36.7	2.0	34.3	1.5	2.3	45.3	5,428	500

Nominal cross section area of conductor	Diameter Under Armour	Armour Wire Diameter	Diameter Over Lead Sheath	Lead Sheath Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	mm	mm	mm	Kg/Km	meter
6x2.5 rm	17.2	1.6	15.2	1.2	1.8	24.0	1,717	1000
7x2.5 rm	17.2	1.6	15.2	1.2	1.8	24.0	1,737	1000
8x2.5 rm	19.4	1.6	17.4	1.2	1.8	26.2	2,049	1000
9x2.5 rm	19.5	1.6	17.5	1.2	1.8	26.3	2,045	1000
10x2.5 rm	20.8	1.6	18.8	1.2	1.8	27.6	2,215	1000
12x2.5 rm	21.4	1.6	19.4	1.2	1.8	28.2	2,320	1000
14x2.5 rm	22.5	1.6	20.5	1.2	1.8	29.3	2,410	500
16x2.5 rm	23.5	1.6	21.5	1.2	1.9	30.5	2,595	500
19x2.5 rm	24.6	1.6	22.6	1.2	1.9	31.6	2,787	1000
21x2.5 rm	25.9	1.6	23.9	1.3	1.9	32.9	3,057	500
24x2.5 rm	28.6	2.0	26.4	1.3	2.0	36.6	3,673	500
30x2.5 rm	30.3	2.0	28.1	1.4	2.1	38.5	4,166	500
37x2.5 rm	32.4	2.0	30.2	1.4	2.2	40.8	4,645	500
40x2.5 rm	33.9	2.0	31.5	1.5	2.2	42.3	5,005	500
50x2.5 rm	38.7	2.5	36.1	1.6	2.4	48.5	6,528	500
61x2.5 rm	40.8	2.5	38.2	1.6	2.5	50.8	7,143	500