


J-YY



These cables are used for telephone and signal transmission for permanent laying on or under plaster , outdoor on walls . Laying underground is not permissible . They are manufactured in acc. with IEC 189 similar to VDE 0815 type J-YY

Construction :

Conductor	Solid plain (or Tinned) annealed copper
Earth wire	Bare copper wire (optional for up to 10 pairs)
Insulation	PVC type TI 1
Sheath	PVC type TM 1 or type 6

Color Code: as IEC 708 or IEC 189 or VDE 0815

Number of Pairs x Conductor Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm	mm	mm	Kg/Km	meter
1x2x0.4	0.7	2.9	12	250
2x2x0.4	0.7	3.8	19	250
3x2x0.4	0.7	4.0	25	250
4x2x0.4	0.7	4.3	30	250
5x2x0.4	0.7	4.6	32	250
6x2x0.4	0.7	4.9	19	250
8x2x0.4	0.7	5.4	19	250
10x2x0.4	0.8	6.0	56	250

J-YY

Number of Pairs x Conductor Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm	mm	mm	Kg/Km	meter
1x2x0.5	0.7	3.2	15	250
2x2x0.5	0.7	4.3	23	250
3x2x0.5	0.7	4.6	28	250
4x2x0.5	0.7	4.9	35	250
5x2x0.5	0.7	5.4	41	250
6x2x0.5	0.7	5.6	47	250
8x2x0.5	0.7	6.2	59	250
10x2x0.5	0.8	6.9	73	250

Number of Pairs x Conductor Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm	mm	mm	Kg/Km	meter
1x2x0.6	0.7	3.4	17	250
2x2x0.6	0.7	4.6	28	250
3x2x0.6	0.7	4.9	35	250
4x2x0.6	0.7	5.3	45	250
5x2x0.6	0.7	5.8	51	250
6x2x0.6	0.7	6.1	59	250
8x2x0.6	0.7	6.8	74	250
10x2x0.6	0.8	7.5	94	250