


Conductor	Stranded (class 2) Plain annealed copper wires 35 mm ² and above compacted conductor
-----------	--

Color Code Options :



Insulation	XLPE
Inner Covering	Extruded PVC
Metal Sheath	Lead Sheath (Cover)
Inner Covering (Bedding)	Extruded PVC
Armour	Galvanized Steel Wires
Over-Sheath	Extruded PVC



Nominal cross section area of conductor	Diameter Under Armour	Armour Wire Diameter	Diameter Over Lead Sheath	Lead Sheath Thickness	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm ²	mm	mm	mm	mm	mm	mm	Kg/Km	meter
5x1.5 rm	14.5	1.25	12.5	1.2	1.8	20.6	1,217	1000
5x2.5 rm	15.6	1.25	13.6	1.2	1.8	21.7	1,369	1000
5x4 rm	17.1	1.6	15.1	1.2	1.8	23.9	1,705	1000
5x6 rm	18.6	1.6	16.6	1.2	1.8	25.4	1,955	1000
5x10 rm	21.1	1.6	19.1	1.2	1.8	27.9	2,414	1000
5x16 rm	24.0	1.6	22.0	1.2	1.9	31.0	2,994	1000
5x25 rm	29.0	2.0	26.8	1.3	2.0	37.0	4,326	1000
5x35 rm	30.8	2.0	28.6	1.4	2.1	39.0	5,011	1000
5x50 rm	35.3	2.0	32.9	1.5	2.3	43.9	6,432	500
5x70 rm	41.1	2.5	38.5	1.7	2.6	51.3	8,844	500
5x95 rm	46.4	2.5	43.6	1.9	2.8	57.0	11,056	500
5x120 rm	51.2	2.5	48.2	1.9	2.8	61.8	13,086	500
5x150 rm	56.9	2.5	53.7	2.1	3.1	68.1	15,714	500
5x185 rm	63.1	3.2	59.7	2.2	3.3	76.0	19,790	250
5x240 rm	71.1	3.2	67.3	2.5	3.6	84.7	23,914	250