

Security Alarm



These cables are used in intruder alarm systems in building Alarm cables are not for use in locations open to the weather without additional protection. They are manufactured in acc. with BS 4737

Construction :	
Conductor	Tinned annealed copper 0.22 mm ² (7x0.2)
Insulation	PVC type TI 1
Sheath	PVC type TM 1 or type 6
Rip cord	Rip cord for jacket easy removal

Color Code:	
2 Core :	RED , YELLOW
4 Core :	RED , YELLOW , BLACK , BLUE
6 Core :	RED , YELLOW , BLACK , BLUE , WHITE, GREEN
8 Core :	RED , YELLOW , BLACK , BLUE , WHITE, GREEN ,ORANGE , BROWN
10 Core :	RED , YELLOW , BLACK , BLUE , WHITE, GREEN ,ORANGE , BROWN , GREY , PINK
12 Core :	RED , YELLOW , BLACK , BLUE , WHITE, GREEN ,ORANGE , BROWN , GREY , PINK , VIOLET , TURQUOISE



Number of Cores x Conductor Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm	mm	mm	Kg/Km	meter
4x0.22	0.5	3.4	20	100
6x0.22	0.6	4.0	28	100
8x0.22	0.6	4.3	34	100
12x0.22	0.7	5.2	50	100