

**A-2Y(St)2Y****2-10 pairs Generally as IEC 60708**

These cables are used for telephone and signal transmission for permanent laying on or under plaster , outdoor . They are manufactured generally in acc. with IEC 60708 similar to VDE 0816

**Construction :**

Conductor	Solid plain (or Tinned) annealed copper
Insulation	HDPE
Static screen	Polyester Tape + Drain Wire(Tinned Copper ) +Al.Polyester Tape
Sheath	Black LDPE

**Color Code: as IEC 60708**

Number of Pairs x Conductor Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm	mm	mm	Kg/Km	meter
2x2x0.4	1.0	4.7	19	2000
4x2x0.4	1.0	5.2	27	2000
6x2x0.4	1.0	5.8	35	2000
8x2x0.4	1.0	6.2	42	2000
10x2x0.4	1.0	6.5	49	2000

# A-2Y(St)2Y



## 2-10 pairs Generally as IEC 60708

Number of Pairs x Conductor Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm	mm	mm	Kg/Km	meter
2x2x0.5	1.0	5.2	24	2000
4x2x0.5	1.0	5.8	35	2000
6x2x0.5	1.0	6.5	47	2000
8x2x0.5	1.0	7.1	58	2000
10x2x0.5	1.0	7.4	68	2000
2x2x0.6	1.0	5.8	30	2000
4x2x0.6	1.0	6.6	46	2000
6x2x0.6	1.0	7.4	62	2000
8x2x0.6	1.0	8.1	77	2000
10x2x0.6	1.0	8.6	92	2000
2x2x0.8	1.0	6.8	47	1000
4x2x0.8	1.0	7.7	73	1000
6x2x0.8	1.0	8.9	100	1000
8x2x0.8	1.2	10.2	132	1000
10x2x0.8	1.4	11.1	163	1000
2x2x0.9	1.0	7.1	53	1000
4x2x0.9	1.2	8.5	90	1000
6x2x0.9	1.4	10.1	129	1000
8x2x0.9	1.4	11.1	161	1000
10x2x0.9	1.4	11.7	192	1000