

A-2Y(St)2Y-T

Generally as IEC 60708

KCI

These cables are used for telephone and signal transmission for permanent laying on or under plaster , outdoor . They are manufactured generally in acc. with IEC 60708 similar to VDE 0816

**Construction :**

Conductor	Solid plain (or Tinned) annealed copper
Insulation	HDPE
Static screen	Polyester Tape + Drain Wire(Tinned Copper) +Al.Polyester Tape
Sheath	Black LDPE
Messenger	High-Tensile Galvanized Steel wires

Color Code: as IEC 60708

Number of Pairs x Conductor Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm	mm	mm	Kg/Km	meter
10x2x0.4	1.4	15.8	117	1000
20x2x0.4	1.4	17.6	154	1000
30x2x0.4	1.4	19.7	192	1000
40x2x0.4	1.4	21.8	228	1000
50x2x0.4	1.4	23.9	264	1000
70x2x0.4	1.4	28.1	375	1000
100x2x0.4	1.4	34.3	467	1000

Number of Pairs x Conductor Diameter	Sheath thickness	Overall Diameter	Weight	Standard Packing Length
mm	mm	mm	Kg/Km	meter
10x2x0.6	1.4	17.9	164	1000
20x2x0.6	1.4	20.5	241	1000
30x2x0.6	1.4	23.4	347	1000
40x2x0.6	1.4	25.1	421	1000
50x2x0.6	1.4	26.7	499	1000
70x2x0.6	1.4	29.3	643	500
100x2x0.6	1.6	34.9	949	500
10x2x0.8	1.4	19.6	220	1000
20x2x0.8	1.4	23.8	380	1000
30x2x0.8	1.4	26.4	506	1000
50x2x0.8	1.6	31.4	780	1000
10x2x0.9	1.4	20.2	249	1000
20x2x0.9	1.4	24.6	437	500
30x2x0.9	1.4	27.3	590	500
50x2x0.9	1.6	34.2	993	500